GATEWAYS

LMC–485-1

Karakteristike

- **Ethernet to 422/485**
- IP TCP/IP - RS422/485 serijski BUS
- Napajanje 12 do 40 V
- IP 20
- DIN montaža

Opis uređaja

Uređaj služi kao RS422/485 serijski RTU/ASCII na Ethernet TCP/IP gateway. Jednostavna konfiguracija i upravljanje putem interneta. Mogućnost povezivanja sa DATAMON cloud serverom.

Inova Tech d.o.o.
Ratka Mitrovica 130, 11090 Belgrade, tel: +381 11 63 100 26
office@inovatechit.com
wwww.inovatechit.com

Legal notice
Reproduction, transfer, distribution or storage of part or all of the contents in this document in any form without the prior written permission is prohibited. All rights reserved. All trademarks mentioned herein belong to their respective owners.
Copyright © 2021 Inova Tech

Specifikacija

Dimenzije: dužina 107 mm, širina 87,5 mm, visina 59 mm
Napon napajanja 12V do 40V DC
Potrošnja: u stand by režimu 10mA
Protokoli: TCP/IP, UDP ARP, DHCP, BOOTP, SNMP, RIP, RARP, HTTP, TFTP, ICMP
DHCP IGMP WebSocket NTP sinhronizacija
Serijski interfejs: RS422/485 1 port brzine do 921600 bps Kleme terminal 2.54mm
Temperatura: -30°C do +60 °C
Ethernet interfejs: IEEE 802.3, IEEE 802.3u 10/100BASE-TX standard 10/100BASE-TX RJ45 port do maksimum 100m
Podešavanje: Web Interface, Web CLI Telnet default IP 192.168.1.61
Security Protocol: TLS/AES/DES3
IP 20
Web OTA Wireless Upgrade
Serijski protokoli: Modbus Transparent Frame

Inova Tech d.o.o.
Ratka Mitrovica 130, 11090 Belgrade, tel: +381 11 63 100 26
office@inovatechit.com
wwww.inovatechit.com

Legal notice
Reproduction, transfer, distribution or storage of part or all of the contents in this document in any form without the prior written permission is prohibited. All rights reserved. All trademarks mentioned herein belong to their respective owners.
Copyright © 2021 Inova Tech