RF Media Converter

RFM–UE

Karakteristike

- **RF 868 Mhz na Ethernet**
- Napajanje 12 do 24 V
- IP 25
- DIN montaža

Opis uređaja

Uređaj služi kao UHF 868 Mhz serijski RTU/ASCII na Ethernet TCP/IP gateway. Jednostavna konfiguracija i upravljanje putem WEB interfejsa. Mogućnost povezivanja sa DATAMON cloud serverom.

Inova Tech d.o.o.
Ratka Mitrovica 130, 11090 Belgrade, tel: +381 11 63 100 26
office@inovatechit.com
wwww.inovatechit.com

Legal notice
Reproduction, transfer, distribution or storage of part or all of the contents in this document in any form without the prior written permission is prohibited. All rights reserved. All trademarks mentioned herein belong to their respective owners.
Copyright © 2021 Inova Tech

Specifikacija

Dimenzije: dužina 107 mm, širina 87,5 mm, visina 59 mm
Napon napajanja: 12V do 24V DC
Potrošnja: u stand by režimu 10mA
Setup protokol: UART AT komande 115200 8 N 1
Radio IC: Texas instruments CC1310
Frekvencija: 861~876.5MHz
Snaga: 14dBm
Sigurnosni protokoli: AES128
IP 25
Protokoli: TCP/IP, UDP ARP, DHCP, BOOTP, SNMP, RIP, RARP, HTTP, TFTP, ICMP
Podešavanje: Web Interface, Web CLI Telnet. Default IP 192.168.1.61
Ethernet interfejs: IEEE 802.3, IEEE 802.3u 10/100BASE-TX standard 10/100BASE-TX RJ45 port do maksimum 100m
Web OTA Wireless Upgrade
DHCP IGMP WebSocket NTP sinhronizacija
Temperatura: -30°C do +70 °C

Inova Tech d.o.o.
Ratka Mitrovica 130, 11090 Belgrade, tel: +381 11 63 100 26
office@inovatechit.com
wwww.inovatechit.com

Legal notice
Reproduction, transfer, distribution or storage of part or all of the contents in this document in any form without the prior written permission is prohibited. All rights reserved. All trademarks mentioned herein belong to their respective owners.
Copyright © 2021 Inova Tech